
This range of elastomeric turret isolator, in two sizes, provide a load range from 9.0 kg to 290 kg at deflections up to 4 mm. The elastomeric element has a top and bottom insert bonded in to allow easy fixing to both the unit and the floor.

Eurovib fully captive mounts for use in mobile and marine applications provide high mechanical strength and isolation efficiency of 75% at speeds of 1250 r.p.m. at maximum load.

Available in eleven load ranges giving wide selection, which, when coupled with good design, provides consistent performance and long life, plus snubbing at resonance and limited movement under shock.

Casing in heat treated alloy with protective finish. Base is slotted providing fixing for holding down bolts.



Dimensions									
Туре	Α	В	С	D	E	F	G	Н	I
CVT/1	60	85	8	37	50	15	40	80	M8
CVT/2	85	115	11	5 0	75	20	55	110	M12

Transmissability									
Deflection	Machine Speed R.P.M.								
in mm	1250	1500	2000	2500	3000	3500	4000		
1	-	-	-	26	16	12	8		
2		-	19	11	7	6	4		
3		23	12	7	5	4	3		
4	25	16	8	5	4	3	2		

Load is carried on enclosed neoprene turret mount which is resistant to ozones, fuel oils, sea water etc. The centre fixing stud incorporates a captivity retainer, provides levelling after loading and allows the mount to be "locked off" during transit. Anti-thrust snubber fitted in the top of the casing provides isolation of fixing stud and ensures horizontal stiffness on the mount increases with deflection and provides minimum movement at maximum thrust.

Load Data									
Type Blue		Yellow	Green	White	Red	Black	Deflec'		
CVT/1	9.0 - 15kg	14 - 22kg	20 - 32kg	27 - 44kg	36 - 60kg	50 - 100kg	3.0 mm		
CVT/2	18 - 48kg	N/A	54 - 86kg	90 - 144kg	135 - 216kg	180 - 290kg	4.0 mm		

NOTE: ALL DIMENSIONS IN MM STANDARD ENGINEERING TOLERANCE +/- 1MM, UNLESS OTHERWISE STATED RESEARCH & DEVELOPMENT IS ONGOING & UNLESS STAMPED CERTIFIED (VALIDITY 3 MONTHS) THIS DATA SHEET IS ONLY CORRECT AT DATE OF ISSUE



EUROVIB (Acoustic Products) Limited

Goodwood House, 86 Holmethorpe Avenue, Redhill, Surrey RH1 2NL Telephone: 01737 779577 Facsimile: 01737 779537

ICTION Drawing No:

Drawing No: GA/026/999/Rev0

Type CVT Neoprene Turret Isolator

GENERAL ARRANGEMENT DRAWING

THE COPYRIGHT OF THIS DRAWING AND THE RIGHT OF REPRODUCTION
THEREOF IS VESTED IN AND BELONGS TO EUROVIB (ACOUSTIC PRODUCTS) LIMITED

SEPT 1999